

MLT

Standard Hydraulic Lift Tables

รถยกแบบโต๊ะยก



**Lifting
Lowering
Transporting
Always at the
correct height**



Foot pedal operated hydraulic lifting.



Standard **

- Full welded steel construction
- Ergonomically designed lifter / transporter features handy hydraulic foot pump to elevate formed-edge platform, reducing strain and fatigue.
- Used for lifting, transporting, positioning, assembling and stacking.
- Easy to operate brakes keeps unit stationary while loading and unloading.

* Pictured here with screw type lowering ** Superior cable type lowering

Model รุ่น		MLT15	MLT30	MLT50	MLT75	MLT100
Capacity น้ำหนักบรรทุก	kg	150	300	500	750	1000
Min. Table Height ความสูงขั้นต่ำโต๊ะยก	mm	220	285	285	420	380
Max. Table Height ความสูงสูงสุดโต๊ะยก	mm	720	880	880	900	990
The Dimensions of Table ขนาดโต๊ะยก	mm	700 x 450 x 36	815 x 500 x 50	815 x 500 x 50	1000 x 510 x 55	1016 x 510 x 55
Castor Wheel ขนาดล้อ	mm	Ø 100 x 25	Ø 125 x 40	Ø 125 x 40	Ø 147 x 50	Ø 127 x 50
Foot Pedal Cycles to Max. Height การเหยียบเพื่อยก		<=28	<=27	<=27	<=45	<=82
Height of Handle from the Ground ความสูงของที่จับจากพื้น	mm	950	990	990	1000	980
Net Weight น้ำหนักสุทธิ	kg	45	77	81	125	122

MLTD

Double Scissor Hydraulic Lift Tables

รถยกแบบโต๊ะยก

Lifts higher for your special requirement !

Model รุ่น		MLTD35	MLTD80
Capacity น้ำหนักบรรทุก	kg	350	800
Min. Table Height ความสูงขั้นต่ำโต๊ะยก	mm	355	445
Max. Table Height ความสูงสูงสุดโต๊ะยก	mm	1300	1500
The Dimensions of Table ขนาดโต๊ะยก	mm	910 x 500 x 53	1220 x 610
Castor Wheel ขนาดล้อ	mm	Ø125 x 40	Ø127
Foot Pedal Cycles to Max. Height การเหยียบเพื่อยก		<=53	<=97
Height of Handle from the Ground ความสูงของที่จับจากพื้น	mm	975	1015
Net Weight น้ำหนักสุทธิ	kg	105	195



* Superior cable type lowering as standard.